

PVC TARPAULIN FOR TRUCK COVER 1000D*1000D 18*18 680GSM

Features

- 680gsm durable materials. All colors are available
- Excellent tensile strength, tear resistance, extremely soft hand feeling
- Waterproof, flame retardant, Anti-UV, Anti-Bacterial, Anti-Mildew, Oil resistant
- Durable, wipe clean and easy to store away

Product Overview



Technical Data Sheet

Item Code		PTTCFX10180680KS	Test Method
Base Fabric		1000D*1000D 18*18	DIN EN ISO2060
Weight (GSM)		680	DIN EN ISO2286-2
Tensile Strength	Warp (N/5cm)	2500	DIN53354
	Weft (N/5cm)	2100	DIN53354
Tear Strength	Warp (N/5cm)	550	DIN53363
	Weft (N/5cm)	450	DIN53363
Peeling Strength	Warp (N/5cm)	100	DIN53357
	Weft (N/5cm)	100	DIN53357
Temperature		-30°C/+70°C	
Flame Retardant		B1/M1/M2/NFPA701	
Lacquering (Optional)		Acrylic/ PVDF	
Special Treatment		Anti-Wicking/Anti-UV/Anti-Aging/Cold Resistant/Osmosis Prevention/Mildew Resistant	

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,
Haining, Zhejiang, China
Tel: +86-573-80776996 Fax: +86-573-80776998
Mob/Skype/Wechat/WhatsApp: +86-15858322153
<mailto:contact@hncomax.com> <https://www.hncomax.com>

